INFINITY
Nanjing Infinity Technology Co.,Ltd.

No. 55 Runfa Road,Jiangning District,Nanjing,China
Tel: +86-025-52634026
Phone & WeChat: +86 13851427688 / 15618213281
Email: inf1188@vip.sina.com



Frame Core Chokes SQ3324Vertical Series

Characteristics：

- Compact Size with Low Leakage Flux due to the O-type SQ ferrite core
- Low Stray Capacitance for broad-frequency noise attenuation
- Single-Layer Winding eliminates risk of interlayer shorts
- High Normal Mode Noise Suppression
- Reduced Winding Time by up to 90%
- High Inductance achieved via proprietary ferrite mixing and sintering technology

Common Applications：

- Switching Power Supplies
- LED Drivers
- Industrial Automation
- Communication Devices
- Household Appliances
- Audio/Medical Equipment

Specifications:

- Rated Voltage: AC/DC 250V
- Operating Temperature: -40°C to +120°C
- Withstanding Voltage:
  AC 2000V for 60 sec or
  AC 2400V for 1 – 2 sec (Line-to-Line)
- Insulation Resistance: ≥100 mΩ (DC 500V)
- Temperature Rise: ≤40°C at rated current

Options：

- Bulk or Tape & Reel packaging
- Custom inductance, wire gauge, and winding configuration
- Alternative ferrite materials for tailored performance
- SMD versions available on request

Model Comparison Table


Test Condition:1KHz/0.3V AT(25 ° C)

Specifications and Electrical Characteristics

INF Code	Inductance	Wire Diameter	Turns	DC Resistance	Applicable Enameled Wire Diameter	Operating Current	Applicable Power
SQ3324-2mH	2.0mH	0.70*3.0	18	30mΩ MAX	1.65	12.6～16.8A	500～1500W
SQ3324-5mH	5.0mH	0.60*1.8	30	40mΩ MAX	1.2	6.5～10.8A	500～1000W
SQ3324-6mH	6.0mH	0.50*2.0	35	100mΩ MAX	1.15	6～10A	500～1000W
SQ3324-18mH	18.0mH	0.30*1.5	59	350mΩ MAX	0.75	4.5~6.75A	500~600W

Dimensions:[mm]

Vertical



Horizontal

In Product Development

INFINITY
Nanjing Infinity Technology Co.,Ltd.

Room 701, Building A1, No. 55 Runfa Road,Jiangning District,Nanjing,China Tel: +86-025-52634026
Phone & WeChat: +86 13851427688 / 15618213281
Email: inf1188@vip.sina.com



1210 SCC SMT Common Mode Line Filter

Characteristics:

·Enormous common mode impedance Z
·Small dimensions
·1:1 turns ratio
·High current ratings
·Climatic category 40/125/21
·Flammability corresponding to UL 94 V-0

Options:

· High common mode impedance Z, small dimensions, 1:1 turns ratio
· High current ratings, UL 94 V-0 flammability, 40/125/21 climatic category
· For common mode noise suppression, power supplies & data lines

Common Applications:

·Suppression of common mode noise
·Power supply system
·Data lines

Physical Properties

Order Code	L_1 (μH)	Z_{max} (Ω)	I_R (mA)	$R_{DC\ max.}$ (Ω)	V_R (V)	V_T (V(AC))
INF-1210-10μH	10	10000	2750	0.04	80	250
INF-1210-100μH	100	40000	1000	0.28	80	250
INF-1210-1000μH	1000	160000	300	2.5	80	250

Technical Specifications

